

EPIGAP Optronik GmbH

Koepenicker Str. 325b
 D-12555 Berlin
 Fon: +49 (0)30 657637 60
 Fax: +49 (0)30 657637 70



Product Data Sheet

UV LED Chip

EOLC-360-34

Rev. 03, 2017

Radiation	Type	Electrodes
Ultraviolet	InGaAlN / sapphire	P + N up

<p style="text-align: right;">Unit : μm</p>	<p>Description</p> <ul style="list-style-type: none"> - Substrate: Sapphire, epitaxial layer: GaN based material - N bonding pad electrode: Au alloy - P bonding pad electrode: Au alloy - Emission area: $200 \mu\text{m} \times 200 \mu\text{m}$ - Bottom area: $280 \mu\text{m} \times 280 \mu\text{m} \pm 40 \mu\text{m}$ - Chip thickness: $75 \pm 10 \mu\text{m}$ - Bonding pad electrodes: (each) $90 \mu\text{m}$ - Electrodes spacing: $130 \mu\text{m}$
---	--


Optical and Electrical Characteristics

$T_{\text{amb}} = 25^\circ\text{C}$, unless otherwise specified

Parameter	Test cond.	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F = 20 \text{ mA}$	V_F	3.2	3.6	4.2	V
Reverse current	$V_R = 5 \text{ V}$	I_R			10	μA
Peak wavelength	$I_F = 20 \text{ mA}$	λ_p	360		363	nm
FWHM	$I_F = 20 \text{ mA}$	$\Delta\lambda_{0.5}$		15		nm
Radiant power*	$I_F = 20 \text{ mA}$	Φ_e	0.5		1.5	mW

*Measured on bare chip on TO-18 header

Spectrum



Art. No. 111 008



We reserve the right to make changes to improve technical design and may do so without further notice. Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.