

## Specification

Picture	Model No.	Description			PK	Inner	Outer	G.W.	Measurement
						Pc/Box	Pc/Ctn	Kg/Ctn	Cbm/Ctn
	YL-T8(4F)-25W	LED T8 tube	Life span: 50000 hours	Material: Alu.+PC	WB	1	25	15	0.083
		Power: 25W	CCT: 4000K-4500K / 6000K-6500K	Beam angle: 140					
		Size: 1498*26*26mm	Power factor: 0.95	Isolated driver					
		Ra>80	IP: 20						
		Lumen: >2450lm @ 4000K-4500K / >2500lm @6000K-6500K							
		Voltage: 85-265V/AC	Body color: Silver White						
	YL-T8(4F)-30W	LED T8 tube	Life span: 50000 hours	Material: Alu.+PC	WB	1	25	16	0.083
		Power: 30W	CCT: 4000K-4500K / 6000-6500K	Beam angle: 140					
		Size: 1498*26*26mm	Power factor: 0.95	Isolated driver					
		Ra>80	IP: 20						
Lumen: > 2950lm @ 4000K-4500K / >3000lm @6000K-6500K									
Voltage: 85-265V/AC		Body color: Silver White							

Remark

- 1.Warranty: 3 years
- 2.Delivery time: 2 - 3 Days