




Features

- : 850nm wavelength range
- : Peak 2W VCSEL by pulse mode operation
- : Multi_mode beam profile
- : High reliability
- : Other configurations available on request

Description




Applications

- : Consumer electronics
- : Safety sensor
- : Illumination light source
- : Gesture sensor light source

Absolute Maximum Ratings

Parameter	Rating
Storage Temperature	-40 to 85 °C
Operating Temperature	-10 to 70 °C
Continuous Forward Current	1 A

Dimensions






Electro-Optics Characteristics ($T_a=25^{\circ}\text{C}$ unless otherwise stated)

Parameters	Symbol	Specified			Unit	Test Conditions
		Min.	Typ.	Max.		
Threshold Current	I_{th}		550		mA	CW
I_{th} Temperature Variation	ΔI_{th}		300		mA	$T_a = -10$ to 70°C
Slope Efficiency	η		1.0		W/A	$I_f = 1$ A
η Temperature Variation	$\Delta\eta / \Delta T$		-0.8		% / $^{\circ}\text{C}$	$T_a = -10$ to 70°C at 1 A
Peak Optical Output Power	P_o		2		W	Peak Pulse Current 2.5 A (12.5% duty ratio)
Peak Wavelength	λ_p	840	850	860	nm	Peak Pulse Current 2.5 A (12.5% duty ratio)
λ Temperature Variation	$\Delta\lambda / \Delta T$		0.06		nm / $^{\circ}\text{C}$	$T_a = -10$ to 70°C at 500mA
Spectral Bandwidth (RMS)	$\Delta\lambda$			2	nm	$I_f = 1$ A
Beam Divergence	\ominus		22		$^{\circ}$	Peak $P_o = 2$ W (FWHM)
Operating Voltage	V_f		2.2	2.6	V	Peak current = 2.5 A
Breakdown Voltage	V_b	-10			V	$I_r = 10\mu\text{A}$
Dynamic Resistance	R_d			1	Ohm	Peak current = 2.3 A

Notes

* These specifications are subject to change without notice.




NOTICE	The inherent design of this component causes it to be sensitive to electrostatic discharge(ESD). To prevent ESD-induced damage and/or degradation to equipment, take normal ESD precautions when handling this product
DANGER	The VCSEL is a class IIIb laser and should be treated as a potential eye hazard. Due to the size of the component, the applicable warning logotype, aperture label, and certification / identification label cannot be placed on the component itself.




Characteristics Curves

CW LIV Curve




CW Power conversion efficiency




Test PKG sample : To-Can type, To-46
 CW Mode : IF step interval 30mA, Delay time 2msec

QCW LIV Curve



QCW Power conversion efficiency



Test PKG sample : To-Can type, To-46
 Test condition : QCW Mode : IF step interval 35mA, 1kHz, 12.5% duty ratio.